

SUHNER®

The new UPK 5-R: 1530 watts – 3 kg small



Maximum performance from minimum dimensions:

The extremely robust design and the high-quality motor and housing ensure a long service life, even under complicated working conditions.

The ergonomic design with the exhaust air directed away from the user, the cowl for keyless adjustments, the guide wheel, the variable handle, and a lockable on/off switch allow reliable and precise handling for fatigue-free working.



 Abrasive expert.

SUHNER



UPK 5-R

Specifications

Power consumption	Mains voltage	Power output	Idle speed	
1530 W	120/230 V, 50/60 Hz	1000 W	1800-4000 min ⁻¹	
Max tool ø	Weight w/o cables	Order no.		
125 mm	3,0 kg	230 V	120 V	240 V
		111 236	111 23703	111 23705

Standard equipment:

Cowl ø 125 x 100 mm with handle, tool holder spindle dia. ø 19 x 100 mm.



Flap brush

Type	ø x width	Shaft/aperture	Max speed	kg	Grain size and order no.			
					100	180	280	
FVVGW 100/100	100 x 100	19 mm	5700	0,310	908 750	908 751	908 752	1



Combi flap brush

Type	ø x width x aperture	Mandrel	Max speed	kg	Grain size and order no.			
					40/M	60/M	120/F	
FVSW 100/100	100 x 100 x 19	FG M 14- 19 x 100	5700	0,535	907 876	907 877	907 878	1

Elastic abrasive flap brush ESW with abrasive belts ESWB:

Elastic flap brush for perfect and smooth grinding of large surfaces.



Type	Measurements	ø aperture	Max speed	Order no.	
ESW 100/100	100 x 100	19 mm	6900	908 736	1

Type	Measurements	for	Max speed	Grain size and order no.			
				coarse	medium	very fine	
ESWB 100 x 100 FV	320 x 100	ESW 100 x 100	5500	908 742	908 743	908 744	10

Type	Measurements	for	Max speed	Grain size and order no.			
				A160 (K120)	A65 (K280)	A45 (K400)	
ESWB 100 x 100 TZ	316 x 100	ESW 100 x 100	2700	908 745	908 747	908 748	10



Individualised application solutions optimise your creation of value.

Every complex grinding task requires its own specific approach. What could be better than testing the various grinding options on your actual problem and measuring their economy and results? This lets you discover and utilise rationalisation potential – exactly what the free SUHNER demo service offers.

Profit from our Know how and ask us for a consultation without obligation! All of our personnel are competent grinding professionals with many years of experience who will be pleased to pay you a visit at your location.

Schweiz/Switzerland
SUHNER Abrasive Expert AG
 Postfach
 CH-5201 Brugg
 Phone 056/464 28 80
 Fax 056/464 28 31
 e-mail: info.sae@suhner.com

Deutschland/Germany
OTTO SUHNER GmbH
 Postfach 1041
 D-79701 Bad Säckingen
 Phone 07761/557-0
 Fax 07761/557-190
 e-mail: info.de@suhner.com

Österreich/Austria
SUHNER SU-matic
 Handelsgesellschaft mbH
 Walkürengasse 11/1
 A-1150 Wien
 Phone 01/587 16 14
 Fax 01/587 48 19
 e-mail: office.at@suhner.com

Italien/Italy
SUHNER Italia S.r.l.
 Via Filotti 2a
 I-24123 Bergamo
 Phone 035/22 06 98
 Fax 035/22 59 65
 e-mail: info.it@suhner.com

Frankreich/France
SUHNER France S.A.
 3ter, Rue Parmentier – BP 98
 F-94140 Alfortville
 Phone 01 49 77 62 90
 Fax 01 49 77 62 39
 e-mail: info.fr@suhner.com

Grossbritannien/Great Britain
SUHNER U.K. Ltd.
 Unit No. 1
 Pool Road Business Center
 Nuneaton CV10 9AQ
 Warwickshire UK
 Phone 02476 384 333
 Fax 02476 384 777
 e-mail: info.uk@suhner.com

Mexiko/Mexico
SUHNER Productos Industriales
 Mexicanos, S.A. de C.V.
 Boulevard Hidalgo 101-B local 3 y 4
 Col. Centro
 San Juan del Rio, Querétaro
 76800 México
 Phone 427/272 3978
 Fax 427/272 8108
 e-mail: info.mx@suhner.com

USA/Canada
SUHNER Industrial Products Corp.
 Hwy. 411 S/Suhner Drive
 P.O. Box 1234
 Rome, GA 30162-1234
 Phone 706/235 80 46
 Fax 706/235 80 45
 e-mail: abrasive.usa@suhner.com

Australien/Australia
SUHNER Australia Pty. Ltd.
 P.O. Box 607
 Rydalmere, NSW 1701
 Phone 02/96 38 66 00
 Fax 02/96 38 77 33
 e-mail: info.au@suhner.com

Indien/India
SUHNER India Pvt. Ltd.
 Plot No. 235 U2
 Bommasandra Industrial Area
 Bangalore 560 099
 Phone 080 78 31 108
 Fax 080 78 31 109
 e-mail: blroffice.in@suhner.com